

REC'D 19 NOV 2004

WIPO

PCT

PCT/1804/52391

PA 1117637

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

January 23, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/519,807

FILING DATE: November 13, 2003

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)



By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS

H. L. Jackson

H. L. JACKSON

Certifying Officer

BEST AVAILABLE COPY

Please type a plus sign (+) inside this box → +

PTO/SB/16 (02-01)
Approved for use through 10/31/2002. OMB 0851-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV 312 06:9 573 Date of Deposit: November 13, 2003

INVENTOR(S)		
Given Name (first and middle (if any))	Family Name or Surname	Residence (City and either State or Foreign Country)
Walter	DEES	EINDHOVEN, NETHERLANDS

☐ Additional inventors are being named on the _____ separately numbered sheets attached hereto

TITLE OF THE INVENTION (280 characters max)
CONSISTENT USER INTERFACE FRONT END FOR REMOTE USER INTERFACES

DIRECT all correspondence to:
CORRESPONDENCE ADDRESS

☒ Customer Number

24737

OR

☒ Firm or Individual Name

Type Customer Number here

U. S. PHILIPS CORPORATION

Address

P. O. BOX 3001

Address

City

BRIARCLIFF MANOR

State

NY

ZIP

10510

Country

USA

Telephone

(914) 945-6000

Fax

(914) 332-0615

ENCLOSED APPLICATION PARTS (check all that apply)

☒ Specification Number of Pages

16

☐ CD(s), Number

☒ Drawing(s) Number of Sheets

4

Other (specify)

☐ Application Data Sheet. See 37 CFR 1.76

METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)

☐ Applicant claims small entity status. See 37 CFR 1.27.

☐ A check or money order is enclosed to cover the filing fees

FILING FEE
AMOUNT (\$)

☒ The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:

14-1270

160.00

☐ Payment by credit card. Form PTO-2038 is attached.

The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.

☒ No.

☐ Yes, the name of the U.S. Government agency and the Government contract number are: _____

Respectfully submitted

SIGNATURE

Date **November 13, 2003**

REGISTRATION NO.: **42,079**

(if appropriate)

TYPED or PRINTED NAME

Daniel J. Plotrowski

Docket Number:

US030450

TELEPHONE

(914) 333-8624

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Alexandria, VA 22313.

The PTO did not receive the following
listed items(s) Page 4 of drawing

CONSISTENT USER INTERFACE FRONT END FOR REMOTE USER INTERFACES

5 The present invention relates to a system and method for a consistent front end for remote and local user interfaces.

Throughout the following text the Glossary and Abbreviations at the end of the description are employed, usually without reference to same. It is to be understood that these terms are used in the sense defined herein if there is a conflict between the ordinary meaning of these terms and the terms defined herein.

10 User interfaces are playing an increasingly important role in home networking. In the area of universal plug-and-play (UPnP), however, almost no standards have been either developed or proposed concerning user interfaces. Developers of user interface (UI) devices, consequently have complete freedom to create applications and user interfaces for controlling services in a home network. Controlled devices, such as an audio device or a DVD+RW
15 device, currently can optionally provide an HTML-page as a user interface. Except using optional HTML-pages they have, in fact, very limited control over the appearance of a user interface that is used on a UI device and can never be sure that their distinguishing features are accessible from these UI devices. Furthermore, some home networking scenarios, such as session migration and the use of multiple output devices simultaneously, are difficult to realize
20 if the ownership of applications and user interfaces belong solely to UI devices.

Remote UI technology is becoming an important technology in this area (next to local UIs) in order to deal with these limitations. PC manufacturers use it to allow applications running on a PC to be used on thin-client devices. Remote UI technology also enables a controlled device, such as a DVD+RW, to offer applications and UIs together with its services
25 to other devices in a home network. This provides a way for developers to maintain ownership of user interfaces and applications since, it is important for participants to be able to distinguish themselves from others. Remote UI technology may also reduce the costs for upgrading UI devices. Therefore, it is likely that the various developers will want to have control over both applications and their user interfaces, and that multiple scenarios of remote
30 UI ownership will co-exist, driven by the marketplace for this technology.

Dealing with user interfaces in a home network is a very complex issue. Because of the large number of developers participating in this technology, very flexible solutions and more open devices are needed in order to meet all their requirements, such as providing a good out-of-the-box experience, being able to handle all kinds of (future) devices, services, applications, different configurations, and multi-user scenarios.

The pair of usage scenarios contained in Appendix A has been promulgated as a basis for developing UPnP remote I/O standards and is typical of home network usage. Considering these usage scenarios as a starting point, the following requirements are important for user interfaces in a home network.

- It must be possible to make use of the functionality that is offered by the services, devices, and applications within a home network via UI devices, preferably using a UI with a developer-specific look & feel. Generic UI devices must provide support for the majority of services/devices/applications that are available in a home network.
- UI devices can have varying capabilities, such as screen size, I/O modalities, etc. User interfaces must be tailored as much as possible to the specifics of the UI device, instead of a free-floating cursor (like in mouse-based systems) on a TV using a standard remote control, and not requiring extensive use of scrolling on a small-screen display. Furthermore, devices can be very resource constrained.
- In order to be successful, home network products must not be more difficult to use than non-networked products. UIs must automatically deal with network configuration changes. In addition, it is important that UIs be consistent (for similar controlled devices as well as among UI devices from different vendors). This means, for example, that:
 - a) preferably, all user interfaces on a generic UI device have the same look & feel, for example, changing volume is done with the same UI for every device and not by having a completely different UI for every developer (e.g. a slider with label "Volume" in one case and a rotating knob with label "Vol. Level" in another case), and

- b) the interaction with a particular device/service/application must be similar among all the UI devices (e.g. not show "Play from DVR" on one UI device, "Play from HD" on a another device and "Play MPEG-2 files" on a PC, because this might create confusion and annoyance among users.

- 5 • The cost for adding networking capabilities to devices must be kept at a minimum.

In addition to the scenarios of Appendix A, the following scenarios are important scenarios that networked user interface technology must be able to support:

- 10 a) Access to content and control of devices: It must be possible for the user to have access to the content that is available in the network as well as the ability to control devices and services, from any compatible device anywhere inside the home, and in a coherent way. It must be possible, for example, to browse/search through all the content as if it were a single database (at least per category, such as through all MP3s), and render the desired content on a user-specified compatible rendering target. Besides content-browsing and device
- 15 control applications, networked user interfaces must also be able to support communication-based applications, e-commerce, information services, games, productivity applications, and so on.
- 20 b) Out-of-the-box experience: It must be easy for the user to add new devices to the home network. Example: User X has just purchased a generic UI device to control his home network. His home network consists of several UPnP devices. After switching on the control device it shows him that it has successfully detected several CE devices and that it has automatically downloaded the newest drivers for most of them. Unfortunately, one of them is not supported. The control device support center has been contacted about the problem and the
- 25 user will be notified automatically when an update is available. In the meantime, the user is advised to download and install some bridging software from the control device support center to the user's PC, with which the user can create simple HTML pages from service descriptions for use in the mean-time.

c) Multiple users: Typically, a home network is used by more than one person. Different family members may want to use the same devices/services/applications of an in-home network at the same time. Therefore, it must be easy to switch to an alternative service or service instance, or to another UI device. It is desirable to share the same resource (e.g. an application) with other people. For example, it must be possible to play a game against each other, where each player has their own UI device and their own view of the same application. Synchronization is very important in such applications in a home network.

d) Personalization: The settings of one user are probably not applicable to other users (e.g. musical preferences in an mp3-jukebox application). Furthermore, there is a need for communication among users. For example, send a "dinner is ready" message to everybody using the home network.

e) Multiple I/O devices: It must be possible to use multiple input and multiple output (i.e. multiple UI) devices for the same application at the same time, to enable UIs where the graphical part of the UI is shown on the TV and the audible part of the UI is redirected to the speakers that are closest to the user. Or, to enable applications such as an intelligent photo browser with which the user can redirect pictures from a mobile device to a bigger screen.

Thus, there is a need for consistency of user interfaces across consumer electronic (CE) devices that are resident in a home network.

The present invention provides a system and method that uses an extensible database of "synonyms" containing constructs of a UI that can be used to replace correspondingly similar UI constructs (also called components) of a CE device, such as labels of UI elements and common user interface patterns, wherein a CE device can make incoming remote UIs more consistent with one another. In a preferred embodiment of a home network, one CE device is typically a UI control device for all the CE devices in the network. On power-up, each of the CE devices sends its UI to the control CE device and it is replaced with a

consistent UI, according to a preferred embodiment, whenever the control device presents that UI to a user.

The database of "synonyms" is used by the control CE device by examining each incoming remote UI for constructs and matching these found UI constructs with known similar "synonyms" in the database. Optionally, those found UI constructs that are not already in the database can be added to the database during this process (by the CE device locally and by downloading the found constructs to a CE device service center). A basic set of these "synonyms" is provided to initiate this system and method.

Note: the above described usage of a database of "synonyms" is not to be confused with using synonyms in speech where the intent is to extend the expressiveness of language by introducing equivalent terms. Here, the intent is to limit the variety of expression to a single consistent set of constructs based on equivalency of a variety of terms.

The foregoing and other features and advantages of the invention will be apparent from the following, more detailed description of preferred embodiments as illustrated in the accompanying drawings in which reference characters refer to the same parts throughout the various views.

FIG. 1 illustrates the process of finding and substituting synonyms for remote UI components according to the present invention.

FIG. 2 illustrates an example of hardware components of a control device within a home network that can be used to perform the present invention.

FIG. 3 illustrates a typical home network with a control CE device and slave CE devices where to embodiments of the present invention can be applied.

It is to be understood by persons of ordinary skill in the art that the following descriptions are provided for purposes of illustration and not for limitation. An artisan understands that there are many variations that lie within the spirit of the invention and the scope of the appended claims. Unnecessary detail of known functions and operations may be omitted from the current description so as not to obscure the present invention.

A preferred embodiment of the present invention is illustrated in FIG. 1, in which one or more controlled devices can provide multiple remote user interface alternatives to the UI device 200. In order for a UI device to know which mechanisms are offered by a controlled device (and vice versa), it must be possible to discover this information. This discovery can be accomplished, for example, by means of a Remote I/O capability description which can be found in a similar way as service descriptions. After this information has been retrieved, a protocol can be chosen that is best suited for the situation.

One or more (remote) RUI definitions 101, which can be in any format, including RDP, X-Windows, VNC, HTTP, HAVi DDI, and UI Fragments, XForms and Java AWT, are taken (simultaneously) as input to an extraction process 102, where the relevant user interface data (i.e. assets) that makes up the user interface (such as labels, bitmaps, widgets) 120 are extracted from the incoming 110 UI definition. If the UI definition input 110 is defined on an abstract level, such as XForms, then this is accomplished in a relatively straightforward manner, as is known in the art. For less abstract or mixed input (such as RDP or HTML) known techniques such as model recovery [1] are applied to extract the relevant UI data 120 and the underlying semantic model of the UI from the incoming concrete UI 110.

After the extraction process 102 the user interface data is analyzed and transformed (syntactically or semantically) 103 using a database of "synonyms" 104:

<u>ORIGINAL</u>	<u>SYNONYM</u>
a, a', a'', a'''	a
b, b', b''	b'
x	x
y, y'	y'
...	...

If a match is found, and analysis of the user interface, with user preferences taken into consideration 107, shows that this replacement will indeed improve the user interface (e.g. by calculating a measure of confidence, and, optionally, through learning from previous analyses and transformations), then the preferred "synonym" replaces the original input 120 and the modified UI information 121 is output, which can be used to render the UI 106:

<u>UI</u>	<u>MODIFIED UI</u>
label a'	label a
label b''	label b'
label c	label c
5 widget x	widget x
widget y	widget y'
...	...

If no match is found, the system connects to the Internet 105 to check on-line thesauri 109 or other relevant databases. If still no match is found, the original value remains in the UI.

10 The preferred "synonym" which is used for transformation can either be a default value (e.g. the first in the list) or one which is selected by a user 108. In a preferred embodiment, the user is allowed to add "synonyms", for example, to give names to devices and processes in a home network by inputting preferences 107. After this transformation step 103, the modified UI 106 is either shown to the user 108 or transferred to another device. In the first
15 case, the synonym transformation process is done on a UI device. In the latter case, the synonym transformation process is offered as a service in the network.

Referring to FIG. 2, the control CE device within the home network of FIG. 3 may include a system with an architecture that is illustrated in the block diagram of FIG. 2. On power up, each slave CE device 101 transmits its RUI 110 to the control CE device 200 for a
20 consistent presentation of its UI to a user by the control CE device 200. The control CE device 200 may include a transceiver 203, an extraction logic module 102, an analysis and transformation module 103, a synonym database 104, a memory 205 and a timer 204. The exemplary system 200 of FIG. 2 is for descriptive purposes only. Although the description may refer to terms commonly used in describing particular control CE devices, the description
25 and concepts equally apply to other processing systems, including systems having architectures dissimilar to that shown in FIG. 2.

In operation, the transceiver 203 is coupled to an antenna (not shown) and to a wireline to transmit and receive data to and from wireless and wired slave CE devices 101.2 and 101.1, respectively. The extraction logic module 102 extracts components of a received slave device
30 UI definition. After the extraction process 102 the extracted UI data 120 is analyzed and

transformed by an analysis and transformation module 103 to replace components of the received slave device UI 120 with matching synonyms from the synonym database 104 to produce a transformed UI definition 121, and is displayed on the user interface module 207 as the interface to the remote (slave) device or is transmitted by transceiver 203 to a second (or third, etc.) control device (not shown). The memory 205 is used by both the extraction logic module and the analysis and transformation module 103 to store learning derived from previous processing of slave CE device UIs and optionally update the synonym database 104 therewith. The timer 204 is used by the logic modules for time dependent processes, such as outdated transformed UIs for slave CE devices that have powered down.

FIG. 3 illustrates a representative home network whereto embodiments of the present invention are to be applied. As shown in FIG. 3, a control CE device 200 is coupled to a plurality of slave wired and wireless CE devices 101, which, through the wireline and wireless links of a home network 206 communicate their UIs to the control CE device 200. A key principle of the present invention is to provide a mechanism to substitute components of a consistent user interface for similar components in each slave CE device UI 101. The control CE device 200 performs an extraction of user interface components and then analyzes and transforms 103 them to finally yield a transformed UI 106 for each slave CE device 101. Although a limited number of CE devices is shown in FIG. 3 for illustrative purposes, it is to be understood that the home network can support communications between a much larger number of CE devices. Thus, the number of CE devices in FIG. 3 should not impose limitations on the scope of the invention. Further, the home network can be based on any of internet protocol (IP) (RFC 791), NETBEUI, Bluetooth, Zigbee, SCP, IEC61883, DVB and ATSC DTV.

In replacing components of the remote user interface, one or more control devices can be employ different replacement paradigms comprising predetermined similarity measures between components of the CUI and the RUI, predetermined improvement measures in the consistency of the RUI after replacement of an RUI component by a CUI component (this can be a cumulative measure depending on the number of such replacements or mappings), predetermined difference measures between components of the CUI and the RUI.

In an alternative embodiment, the control device also has one or more local UIs (LUIs), i.e. a user interface for a local application (see Glossary term "Application"), that it can display, in addition to displaying RUIs. Since these LUIs may contain some user interface constructs (components), which are similar to constructs (components) used in an incoming RUI, it is useful to make the incoming RUIs not only consistent with each other but also with LUIs (so if the label "Play from DVR" is the preferred synonym, then this label has to be used in the RUIs as well as the LUIs). In a preferred embodiment, the synonym that is chosen in the transformation process 103 is the synonym that is used in an LUI, in order to make the incoming RUIs more consistent with LUIs of a control device.

While the preferred embodiments of the present invention have been illustrated and described, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the present invention. In addition, many modifications may be made to adapt to a particular situation and the teaching of the present invention can be adapted in ways that are equivalent without departing from its central scope. Therefore it is intended that the present invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out the present invention, but that the present invention include all embodiments falling within the scope of the appended claims.

Claims:

1. A method for a consistent user interface (CUI) on a control device providing access to at least one network device having a remote user interface (RUI), comprising the steps of:
 - providing the CUI;
 - mapping the RUI to the CUI; and
 - displaying by the control device at least a part of the CUI instead of the RUI as a user interface to the network device.
2. The method of claim 1, wherein:
 - the providing step further comprises the steps of:
 - receiving by the control device an RUI definition comprising at least one RUI component;
 - providing the CUI comprising at least one CUI component optionally pre-set as a synonym for said at least one RUI component; and
 - the mapping step further comprises the step of replacing the received at least one RUI component with said pre-set synonym CUI component by the control device whenever the control device displays a user interface to the network device.
3. The method of claim 2, further comprising the step of transmitting the RUI definition by the at least one network device.
4. The method of claim 3, wherein said transmitting step further comprises the step of on power-up, transmitting the RUI definition by the at least one network device.
5. The method of claim 3, wherein said transmitting step further comprises the step of transmitting the RUI definition using a network based on at least one of IP (RFC 791), NETBEUI, Bluetooth, Zigbee, SCP, IEC61883, DVB and ATSC DTV.

6. The method of claim 5, wherein said transmitting step further comprises the step of transmitting the RUI definition using a protocol based on at least one of RDP, X-Windows, VNC, HTTP, HAVi DDI, and UI Fragments.

7. The method of claim 5, wherein said receiving step further comprises the step of using by the at least one network device for the RUI definition a UI description format based on at least one of HTML, XML, Macromedia, Flash and Java.

8. The method of claim 3, further comprising the step of sending the provided CUI to at least one of the at least one network device and a second control device.

9. The method of claim 7, further comprising the step of transmitting a RUI definition by at least a second network device to the control device using at least one of a different protocol selected from the set consisting of RDP, X-Windows, VNC, HTTP, HAVi DDI, and UI Fragments and a different UI description format selected from the group consisting of HTML, XML, Macromedia, Flash and Java than the corresponding protocol and description format used by the at least one network device.

10. The method of claim 1, wherein:
the RUI and CUI comprise at least one RUI component and at least one CUI component, respectively; and
further comprising the steps of:
extracting said at least one RUI component;
determining if said at least one CUI component is a synonym for the extracted at least one RUI component; and
wherein, said mapping step further comprises the step of
if said at least one CUI component is determined to be a synonym for the extracted at least one RUI component, mapping the at least one extracted RUI component to the determined said at least one CUI component.
11. The method of claim 10, further comprising the step of finding at least one CUI component that satisfies a predetermined similarity measure to said at least one RUI component for a plurality of network devices.
12. The method of claim 10, further comprising the step of finding at least one CUI component that satisfies a predetermined consistency measure of the mapped at least one RUI component.
13. The method of claim 10, wherein said determining step further comprises the step of searching at least one of a thesaurus and a synonym database for a synonym of the extracted at least one RUI component that matches said at least one CUI component.
14. The method claim 13, further comprising the step of storing said matching synonym determined from the thesaurus in the synonym database for the extracted at least one RUI component.
15. The method of claim 14 wherein said at least one thesaurus is located on a second network and said at least one network device is located on a first network.

16. The method of claim 15, wherein said second network is the Internet.
17. The method of claim 15, wherein said first network is a home network and said network device is a consumer electronic device.
18. The method of claim 1, wherein said at least a part of the CUI is determined according to a set of user preferences.
19. The method of claim 1, wherein:
said at least one network device further comprises at least one application local to the control device and said RUI further comprises at least one local user interface (LUI) to said at least one local application.
20. The method of claim 10, wherein:
said at least one network device further comprises at least one application local to the control device and said RUI further comprises at least one local user interface (LUI) to said at least one local application.
21. A method for a slave network device to replace a remote user interface (RUI) with a consistent user interface (CUI), comprising the steps of:
transmitting by the slave network device the RUI to a control network device; and
replacing by the control network device at least a part of the transmitted RUI with at least a part of the consistent CUI by the method of claim 1.
22. A control device that provides a consistent user interface (CUI) in a network of at least one slave device having a remote user interface (RUI), comprising:
a transceiver for receiving the RUI;
an extraction logic module configured to extract at least one component of the RUI;
a database that is configured to store synonyms of components of an RUI; and

an analysis and transformation module configured to

- i. map the extracted at least one component of the RUI to a component of the CUI according at least one of the synonyms stored in said database and a thesauri,
- ii. store the mapping in a memory,
- iii. optionally update the synonym database with the mapping, and
- iv. provide a user interface to the at least one slave device according to at least a part of the mapping of the extracted at least one component of the RUI.

23. The control device of claim 22, further comprising:

at least one local user interface (LUI) to at least one local application;

wherein,

said extraction logic module is further configured to extract at least one component of the LUI;

said database is further configured to store synonyms of components of an LUI;

said analysis and transformation module is further configured to

v. map the extracted at least one component of the LUI to a component of the CUI according to at least one of the synonyms of components of an LUI stored in said database and a thesauri,

vi. provide a user interface to the at least one local application according to at least a part of the mapping of the extracted at least one component of the LUI.

24. The control device of claim 22, wherein said analysis and transformation module is further configured to:

vii. accept a set of user preferences; and

viii. provide said at least a part of the mapping in accordance with the set of user preferences.

25. The control device of claim 22, wherein the thesauri is accessed via another network.

26. The control device of claim 25, wherein the another network is the Internet.
27. The control device of claim 22, wherein the slave device is a consumer electronic device.
28. The control device claim 27, wherein the network is a home network.
29. The control device of claim 22, wherein the network is a home network.

ABSTRACT

5 A method and device for providing a single consistent user interface based on replacing disparate user interface constructs (components) with equivalent constructs (components) from a "synonym" database of user interface constructs (components). The database is initiated with a set of foundational "synonym" constructs (components) and extended with user interface constructs (components) as they are discovered during reduction of an inconsistent user interface to a consistent state.





FIG. 1






FIG. 2




FIG. 3

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.